





Integration of Safety in Design in MOX Fuel Fabrication Facility
Sue King

MOX Safety Fuels the Future



Sue King




- B.S. degree in Chemical Engineering from Virginia Tech
- Started her career working at the Charleston Naval Yard refueling nuclear submarines.
- Worked for the Department of Energy for about a decade in various positions at SRS and Pantex.
- Worked for the SRS M&O contractor for about a decade.
- Since 2006, she has worked for Shaw AREVA MOX Services on the MOX project. Her current position is VP of Projects.



U.S. Pu Disposition Program









Regulatory Regime

- U.S. Congress mandated (Public Law 105-261, 17 October 1998, Section 3134) the MOX Fuel Fabrication Facility will be:
 - Licensed and regulated by the NRC
 - Comply with Occupational Safety and Health Administration Act of 1970
- DOE and NRC requirements met for Physical security
- NRC requirements for MC&A
- MOX Services is the licensee



Applicable Regulations



- 10 CFR 70, Domestic Licensing of Special Nuclear Material
- 10 CFR 20, Standards for Protection Against Radiation
- 10 CFR73, Physical Protection of Plants and Materials
- 10 CFR 74, Material Control and Accounting for Special Nuclear Material
- 10 CFR 50 Appendix B, Quality Assurance Criteria for Nuclear Power Plants and Fuel Reprocessing Plants.



Reference Plants











Total Project Cost

• Concrete:

Reinforcing Steel:

• Cable Tray:

Power/control Cable:

• Process piping:

Gloveboxes:

• Cells:

Analytical Lab:

\$4.86 B

170,000 cubic yard

35,000 tons

47,000 linear feet

3,600,000 linear feet

85 miles

~ 200

24

~85 gloveboxes

>30,000 analyses/year

MOX Safety Fuels the Future







| • | Submit Construction Authorization Request (CAR) to NRC | 2/2001 |
|---|---|----------|
| • | SER and NRC authorization to start construction | 3/2005 |
| • | DOE authorization to start construction (CD 3) | 4/2007 |
| • | Start MFFF Construction | 8/2007 |
| • | End of Construction | 6/2015 |
| • | Begin Hot Startup (Pu in plant) | 10/2016* |

^{*}The construction schedule includes 16 months of contingency. Hot Startup is currently tracking to begin in summer of 2015.



Construction Authorization Request



- Developed and submitted 2/2001
- ~2000 pages
- NRC issued ~250 Requests for Additional Information (RAIs)
- 4 years from time of submittal until NRC issuance of SER
 - Updated during NRC review
- Based on conceptual design and early preliminary design
- Defines safety systems at the system level



Start of Construction August 1, 2007







Operating License Application



- Submitted to NRC 9/2006
- Document Set
 - License application (2000 pages)
 - Integrated Safety Analysis Summary (3800 pages)
 - Fundamental Nuclear Material Control Plan
 - Classified Matter Protection Plan
 - Physical Security
 - Physical Protection Plan
 - Training and Qualification Plan for Security Personnel
 - Safeguards Contingency Response Plan
 - Emergency Plan Evaluation
 MOX Safety Fuels the Future



Document Hierarchy



Submitted NRC

Available on site

License Application

Programmatic

Integrated Safety Analysis Summary

Demonstration

Integrated Safety Analysis

NSEs, NCSEs, HazOps, Calculations

Project Documents

BODs, SDDs, P&IDs, Calculations, Specifications, etc



Integrated Safety Analysis



- Systematic analysis to identify
 - Internal and external hazards
 - Potential event sequences
 - Likelihood and consequences (unmitigated)
 - Identify SSCs at the component level and activities of personnel relied on to mitigate or prevent event sequences
 - Demonstrate Items Relied on For Safety (IROFS) are effective, reliable, and available to meet specified performance criteria



ISA Continued



- Receptors
 - Facility worker (at location of hazard)
 - Site worker (100m from release point)
 - Individual Outside Controlled Area (IOC)
 - Environment
- Controlled Area boundary is about 160m from stack
- Both chemical and radiological hazards
- Must mitigate events with high consequences to "Highly Unlikely" and events with intermediate consequences to "Unlikely"







| Consequence Category | Facility and Site Worker | Individual Outside Controlled Area |
|-------------------------|---|---|
| High | TEDE > 100 rem CC > AEGL3, ERPG3, TEEL3 | TEDE > 25 rem CC > AEGL2, ERPG2, TEEL2 |
| Intermediate | 100 rem > TEDE > 25 rem *3 > CC <u>></u> *2 | 25 rem > TEDE > 5 rem *2 > CC <u>></u> *1 |
| Low | Less than above | Less than above |







CONSEQUENCE

Intermediate High

Low

| No IROFS | IROFS | IROFS |
|----------|----------|----------|
| No IROFS | No IROFS | IROFS |
| No IROFS | No IROFS | No IROFS |

Highly Unlikely

Unlikely

Not Unlikely

LIKELIHOOD

MOX Safety Fuels the Future



Items Relied on For Safety Design Criteria



- Same criteria for systems protecting workers and public
- Robust design that is not susceptible to single-failure
- Consensus Codes and Standards
- Environmental qualification
- Failure detection







- Perform design verification to ensure IROFS are appropriately incorporated into design
- Identify additional layers of controls for defense-in-depth
- Conduct Human Factors Engineering evaluations of administrative controls and human actions
- Update LA, ISA-S as needed during NRC review process
- Annual updates after NRC license received







- Overall Project is 37% complete
- Construction is 18% complete
- NRC Review of LA to-date
 - > 100 review meetings
 - − ~ 600 RAIs
 - First round of RAIs complete
 - ~\$10 million billed by NRC to pay for their review time
 - No significant design changes
- SER scheduled to be complete 2010



June 11, 2009









Conclusion

- Integration of safety into the design follows ISMS principles
 - Identify the hazard
 - Mitigate or prevent the hazard through design
 - Demonstrate that the public, workers, and environment are not adversely affected by the hazard
- Some differences from DOE regulated plutonium glovebox facility

http://www.moxproject.com